



2400BHP PEACE SPECIFICATION

PRINCIPAL PARTICULARS

Port of Registry : Singapore
 Year Built : 2008
 Official Number :
 IMO Number :
 Call Sign :
 Classification : NKK Ocean Going Tug
 Gross Tonnage : 273
 Net Tonnage : 82

Length Overall : 31.100M
 Breadth Moulded : 8.600M
 Depth Moulded : 4.350M
 Draft Moulded : 3.600M

Trial Speed : 11.5 knots
 Basic Bollard Pull : 32.65 tonnes

MACHINERY

Main Engine : CUMMINS KTA 38M2 2 x 1200
 Bhp / 1800rpm
 Gear Box : Reintjes Ratio 5.96:1
 Propeller : 2 x Solid Fixed Pitch Propellers
 Main Generator : 2 x CUMMINS 78kw,
 415/3/50
 Endurance : 35 Days

DECK MACHINERY

Anchor Windlass : speed of 10m/min (19mm)
 Tow Winch : Towing winch 80Ton Brake
 Holding one layer static
 Towing Wire : 44mm x 700mtr
 Towing Hook : 1 x 40 tons

NAVIGATION & COMMUNICATION EQUIPMENT

EPIRB GME Type MT401FF : 1
 VHF-FM Receiver : 1
 Echo Sounder : 1
 GPS FURUNO GP 32 : 1
 Magnetic Compass c/w : 1
 Reflector Compass
 Radar FURUNO 1715 : 1
 SSB Transceiver ICOM IC-M710 : 1
 Immasat C : FURUNO
 Navtex : FURUNO
 Satelite Phone : 1

AUXILIARY EQUIPMENT

F.O. transfer pump : 1 x 8m³/hr @ 20m head
 Bilge & Ballast pump : 1 x 28m³/hr @ 27m head
 GS pump & Fire pump : 1 x 28m³/hr @ 27m head
 Oily water separator : 0.25m³/hr

TANKAGE

Fuel oil : 188 tonnes approx
Fresh water : 64 tonnes approx

FIRE FIGHTING SYSTEM

Firemain : 4 x 1½ (38mm) bronze hydrants
are to be installed
Fire Buckets : 6
Axe : 1
Portable Fire Pump : 1 x ø2"

ACCOMMODATION

1 x 8 berth cabins : 9 men
2 x 1 berth cabins : 2 men
Total complement : 11 men

LIFE SAVING EQUIPMENT

Life Raft : 2 sets for 10 persons
Life Buoy : 8 sets
Fireman Outfit : 1 complete set
Life Jacket : 16 sets
Parachute Distress : 12 units
Smoke Signal : 2 sets
Work Vest : 16 sets

**PARTICULARS GIVEN HEREIN ARE ENTIRELY WITHOUT WARRANTY AS TO CORRECTNESS
INTERESTED PARTIES MUST SATISFY THEMSELVES BY INSPECTION OR OTHER MEANS**